

# LUBIT

DISTRIBUTORS OF

**TEK STAR**  
TOTAL PROTECTION LUBRICANTS

10 Argyle Road, Kingston 10.  
(876)649-9540/ (876)648-6424  
www.lubitltd.com

# TEK STAR

LUBRICANTS

## TOTAL PROTECTION

TEK SAE ND provides service for older engines operated under such mild conditions that the protection of compound oil is not necessary.

This category should be used only when specifically required by the engine manufacturer.

TEK SAE ND proporciona servicio para motores antiguos operados bajo condiciones tan suaves que la protección del aceite compuesto no es necesaria.

Esta categoría sólo debe utilizarse cuando el fabricante del motor lo requiera específicamente.

### TYPICAL PHYSICAL CHARACTERISTICS

Specifications / Especificaciones		30	40	50
Gravity, API	ASTM D-286	24.5	23.5	23.0
Flash Point, F	ASTM D-92	400	430	440
VIS, cSt @ 100°C	ASTM D-445	10.2	13.5	16.7
Viscosity Index	ASTM D-2270	50	50	50
ASTM Color	ASTM D-1500	4	4.5	5

These are typical values subject to stringent industry tolerances. Consult the Material Safety Data Sheet (MSDS) for safety and handling information.

Estos son valores típicos sujetos a las tolerancias estrictas de la Industria. Para el manejo del producto consulte la hoja de seguridad (MSDS)



Web: [www.tekstarlubricants.com](http://www.tekstarlubricants.com)  
email: [yhansen@portconsolidated.com](mailto:yhansen@portconsolidated.com)  
Product Information: 1-305-4504685  
MSDS Requests: 1-305-4504685



# TEK SAE 30, 40, 50 ND

# LUBIT